

Utility AC Labelling System (Model UT2mAC)

The AC type Utility label applying system was developed to satisfy application needs for a rugged and reliable basic automatic labelling system. The system incorporates a zero maintenance robust AC motor.

Typical applications of this labeller are parallel labelling with pre-printed labels, coupons, or closure labels onto products or packaging being transported by the customer's existing material handling devices.

- Versatile to cover a wide variety of label applications
- Label applicator with 150mm label web capacity
- Zero Maintenance AC motor
- T-stand with Hand Crank Height Adjustment
- Side, top, or bottom mounting

Options Available

- Lateral Handcrank Adjustment
- Clear label tracer upgrade
- Power unwinds and rewind
- Collapsible rewind
- 200mm roller set upgrade
- Web break detector
- Low web detector

Speed: Variable, 7m/min to 30m/min, upgradeable

Indexing Accuracy: +/- 2mm at 30m/min typical

Label Roll Diameter: 250mm maximum OD with 76mm Core

Web Width: 19mm to 150mm

Label Length: 20mm to 300+mm

Line Voltage: 120VAC, 5A, 1PH, 60Hz

Electrical Protection Rating: NEMA 12 (IP 55)



Allow us to learn more about your specific labelling needs by calling 1-888-250-1524 or send an e-mail inquiry to sales@labelling.com.



1435 Bonhill Rd Units 31-32 • Mississauga, ON L5T 1V2 • CANADA

Tel: (905)564-2794 • Fax: (905)564-2793 • sales@labelling.com

